



**BUSHING REDUCING - BR (Male to Female ISO Tapered Pipe Threads)**

| Pipe Size |        | Dimension |      |       | Working Pressure | Part No.          |
|-----------|--------|-----------|------|-------|------------------|-------------------|
| Male      | Female | A         | E    | F     | PSIG             |                   |
| 1/4       | 1/8    | 25.4      | 7.1  | 14.28 | 6000             | BR-250-125-RT/PF  |
| 3/8       | 1/4    | 28.6      | 9.5  | 19.05 | 5300             | BR-375-250-RT/PF  |
| 1/2       | 1/4    | 29.4      | 11.1 | 22.2  | 6400             | BR-500-250-RT/PF  |
| 3/4       | 1/4    | 31.0      | 11.1 | 27.0  | 6400             | BR-750-250-RT/PF  |
| 1/2       | 3/8    | 29.4      | 11.1 | 22.2  | 4600             | BR-500-375-RT/PF  |
| 3/4       | 3/8    | 39.7      | 14.7 | 27.0  | 5300             | BR-750-375-RT/PF  |
| 3/4       | 1/2    | 39.7      | 15.9 | 27.0  | 4900             | BR-750-500-RT/PF  |
| 1"        | 1/2    | 39.7      | 18.3 | 35.0  | 4600             | BR-1000-500-RT/PF |
| 1"        | 3/4    | 44.5      | 22.2 | 35.0  | 4200             | BR-1000-750-RT/PF |

Dimensions for reference only  
and are subject to change.